

Wafer Type SS Butterfly Valve

Fig. 2335P

Stainless Steel Body • Extended Neck • Geometric Drive • Molded-In Seat Liner
•Wafer Type

Sizes 2" through 12"

SPECIFICATION


Design in accordance with EN593,ISO5211
Flanges comply with EN1092-2,ISO 7005
Pressure test according to standards EN12266

TECHNICAL DATA

Working Pressure:10 bar
Dimensions: DN50~DN300
Test Pressure:Shell:15bar Seal:11bar
Working Temperature: -12°C~135°C PTFE Seat

MATERIAL LIST

Part Name	Materials	Specification
Body	Stainless Steel	A351 CF8
Stem	Stainless Steel	BS970 410 S 21
	Stainless Steel	BS970 431 S 29
Seat	PTFE(Viton/EPDM)	
Bushing	PTFE	
	Bronze	EN 1982 CC491K
O-Ring	EPDM / NBR	
Disc	Stainless Steel	A351 CF8
	Stainless Steel	A351 CF8M
Drive unit	Malleable Iron	
	Cast Iron	




DIMENSIONS

DN	mm	50	65	80	100	125	150	200	250	300
	inch	2	2-1/2	3	4	5	6	8	10	12
A		156	170	175	176	206	225	256	302	360
B		64	76	91	104	129	142	176	209	249
L		42	44.5	44.5	51	54.5	54.5	60	67	76
F		195	195	195	266	266	328	386	386	386

Visit our website for the most current information.

Wafer Type SS Butterfly Valve (continued)

Fig. 2335P


Dimensions

DN	mm	50	65	80	100	125	150	200	250	300
	inch	2	2-1/2	3	4	5	6	8	10	12
A		156	170	175	176	206	225	256	302	360
B		64	76	91	104	129	142	176	209	249
L		42	44.5	44.5	51	54.5	54.5	60	67	76
L1		133	133	133	133	133	133	223	223	228
L2		120	120	120	120	120	120	204	204	227
ØW		150	150	150	150	150	150	280	280	280

Visit our website for the most current information.